

## Construction & combinations

2 tapes bonded together back-to-back using the A-glue  
 - hook & loop - hook & hook  
 - mushroom & velours - loop & loop  
 - hook & velours - mushroom & mushroom

## Colours & quantities

all combinations in all the colours of our shade card: min. 100 m

## Info on A-glue

see technical data sheet E-101

## Standard widths

12 - 16 - 20 - 25 - 30 - 38 - 50 - 100 mm

it is possible that widths are slit from a wider tape

## Thickness fastener

based on	- hook & loop	: 4,5 mm	(+/- 0,5 mm)
	- mushroom & velours	: 3,5 mm	(+/- 0,5 mm)
	- hook & velours	: 4,0 mm	(+/- 0,5 mm)
	- hook & hook	: 3,9 mm	(+/- 0,5 mm)
	- loop & loop	: 4,0 mm	(+/- 0,5 mm)
	- mushroom & mushroom	: 3,4 mm	(+/- 0,5 mm)

## Weight (average weight)






based on	- hook & loop	: 800 gr/m2 (+/-10%)
	- mushroom & velours	: 750 gr/m2 (+/-10%)
	- hook & velours	: 750 gr/m2 (+/-10%)
	- hook & hook	: 800 gr/m2 (+/-10%)
	- loop & loop	: 800 gr/m2 (+/-10%)
	- mushroom & mushroom	: 800 gr/m2 (+/-10%)

impact of edges is more important in smaller than in larger widths

## Colour fastness

EN 20105-B02	light	5	on a scale of 8
DIN/ISO 105 X12	rubbing wet & dry	4	" " " " 5

## Cleaning instructions

washing	bleaching	ironing	dry-cleaning	tumble drier
				

## Resistance to temperatures

from - 10°C to + 70°C

## Applications

* medical & orthopedic applications	* home & garden
* cable & cord holder	* boat, camping car, tent, car or van
* outdoor & sports	* office & storage uses

## Fastening values

info on hook & loop (st.)	: techn. data sheet E-003
info on mushroom & velours (st.)	: techn. data sheet E-004
info on hook & velours (st.)	: techn. data sheet E-005

## Tests by user & guarantees

**The information above only serves as a general guideline.  
 We advise any user to determine the suitability  
 of the intended application through tests performed by himself.**

All information, technical advice, recommendations & descriptive material on this product are based upon tests which are generally reliable, although we cannot fully guarantee the accuracy of these tests. The buyer, who is a professional user, will be bound to carry out all tests himself, in order to verify whether the goods are suited and can be used safely for the intended purpose. The only obligation of the seller may consist in replacing the goods of which the imperfection has been proven, insofar as the seller can be held liable for the imperfection under the present conditions. The buyer will protect and hold harmless the seller against any claim whatsoever which could be made by the private enduser on the account of his product liability. In the same way, the buyer will safeguard the seller for each claim made by third parties, exceeding the limitation of liability as stipulated herewith. In addition, we serve ourselves the right to subject the products to technical changes without prior notice. Please make sure that you have the latest version of the technical data sheet.